Luna Bevel 26×142 Hidden Nailing

LUNAWOOD

CLADDING & PANELING

Luna Bevel 26x142 Hidden Nailing is a premium Thermowood cladding for facades.





PRODUCT DETAILS

Size	26x142
Class	LunaThermo-D
Surface	Planed
Species	Nordic spruce, *Picea abies*
Lenghts	3,9 - 5,4 (availability varies) Length package in 30 cm modules
Utility data	Coverage width 121 mm, 8,2 m² Weight average ~1,4 kg/m ~11,4 kg/m²
Packaging	Package size 192 pcs (half package) 4 pcs/bundle, 48 bundles/package. Package covered by Lunawood plastic hood on 5 sides
Article	26x142 Bevel HN Thermo-D WW SAP A
Product specifications	Tolerances, quality and installation based on. Lunawood general rules and instructions. Nominal size: 32x150 DoP: No 002
	Also available fire protected

LUNAWOOD TECHNICAL DATASHEET

Essential Characteristics	Spruce (Picea abies)	Harmonized European standard
Density	420 kg / m³	SFS-EN 317
Reaction to fire class	D - s2, d0	SFS-EN 13501-1:2018
Screw traction resistance	-	SFS-EN 13446
Thermal conductivity	0,09 W/(m·K)	EN ISO 13787 + EN 12667
Durability class	Class 2 Thermo-D	EN 350-1
Use class	Class 3 Thermo-D	EN 335
Stability, shrinking and swelling	Tangential fibre direction 4 % Radial fibre direction 2 %	SFS-EN 317
Equilibrium Moisture	7,3 %	EN 13183-1
Brinell Hardness	1,52 N/mm²	SFS-EN 1534
Janka	1700 N	ASTM D143-94
TVOC	Thermo-D 0,022 mg/m²h	ISO 16000-9:2006 SFS-EN 16516:2017
CO2 emissions (EPD)	117 kg CO2 eq/m³	Lunawood EPD

Use QR code by phone or click it to open to Your browser

Product documents

Design tools

Version: 2/2025